

Machine Specification	2 Ribbon - KWS 2R	3 Ribbon - KWS 3R	4 Ribbon - KWS 4R
Number of Row	2	3	4
Baking Wheel Diameter (mm)	2,000	2,000	2,200
Product Diameter (mm)	8 - 16 or 17 - 24 (choose either one)		
Product Length (mm)		30-260	
Capacity (pcs/min) *with product Size L: 100 mm D:10 mm	180 - 200	270 - 300	380 - 400
Number of Torch Burner (pcs)	6 LH + 6 LR	10 LH + 10 LR	15 LH + 15 LR
Number of Infrared Burner	8	11	9 (Bigger Size)
Electric Consumption	7.5	9.5	11.5
Power Supply	AC 415V, 3 Phase, 50 Hz/60 Hz		
Temperature Sensor	Standard: Thermocouple in Chamber Optional: Infrared Temperature Sensor on Baking Wheel		
Gas Mixture System	Automatically by Inverter Blower		
Flame Detector	Included		
Driver Motor	Germany made AC motor with variator		
Cutting System	Servo Motor Using Inverter		
Equipment Supplied with	1 Set 1 st Color Batter Supply System with Gear Pump 1 Set 2 nd Color Batter Supply System with Gravity Flow 1 Set Filling Double Jacket Supply System with Gear Pump 1 Unit Pressure Tank for Gluing System		
Material			
Body	Double Wall, heat insulated by Rockwool with SUS plate		
Baking Wheel	Cast Iron		
Batter Pump	Stainless Steel Gear Pump		
Filling Cream Pump	Double Jacket Stainless Steel Gear Pump		
Dimension L x W x H (mm)	3,000 x 1,900 x 2,300	3,000 x 2,100 x 2,300	3,000 x 2,500 x 3,000
Approximate Weight (Kg)	3,200	3,300	4,000

All specification can be changed refer to latest technology without prior notice